

Tracks



Terrestrial examples:



- 300 hour life (10 000 km)



ODG-Argo Metallic Track development




▣ Gen II Tracks


- Tandem Toothed Wheels With Alternating Asymmetrical Cable Clamped Segmented System (TWACS)
- One-way introvert drivers



- Tensioner system prevents derailment and jamming.
- Spring-loaded undercarriage follows ground contours and keeps track aligned.



- Spring loaded bogie wheels follow central groove and distribute ground pressure
- Semi-cylindrical blocks clamp cable and interface with driver
- Alignment pins ensure that the track has adequate lateral rigidity



Gen II mass = 147 kg per rover (compared to 72 kg per rover for the Tweel / Goodyear Non-Pneumatic wheel).

Durability testing – Gen II:




Sand Testing

- ▣ Compared tracks to baseline rubber tires
- ▣ Simulated vehicle weight at 200, 400, and 550 kg (1 G)
- ▣ Conducted in very fine grained sand




Baseline Rubber tire




Gen II TWACS

Tractive Force for Tracks




Tires vs. Tracks




TWACS Evolution - Gen III

- More advanced materials
- Minor design changes



TWACS Evolution - Gen III

- ▣ Reduced mass
 - **20.4 kg** per track (down from 27.3 kg)
 - Total Gen II track system mass - 147 kg
 - Total Gen III track system mass - **112 kg**
 - Baseline wheels - 65 kg
- ▣ Increased resistance to derailment and durability
 - Raised height of central track lug guides
 - Increased alignment pin contact area.



Maiden Voyage Gen III Tracks



Future work

➤ Mobility Testing

- Traction testing – sand, rocks, slopes, etc.
- Field tests at analogue site

➤ Durability Testing

- ODG proving grounds
- Analogue site

➤ Track over wheel design

- Increased redundancy

Fin

Questions??

Acknowledgments:

Neptec Design Group

NRC Canada

Canadian Space Agency



The Most Versatile Off-Road Vehicle in the World

