



RIDER and SPIDR: Open-Access Complementary Facilities for Planetary Terramechanics Investigations


J. Long-Fox¹, H. M. Sargeant², M. P. Lucas³, C. R. Neal³, J. Conway¹, M. Conroy¹, A. Glover¹, A. Hacker¹, A. Madison¹, G. Blandin¹, P. Easter¹, and D. Britt¹

jared.long-fox@ucf.edu

¹University of Central Florida – Department of Physics

²University of Leicester – Space Park Leicester

³University of Notre Dame - Department of Civil and Environmental Engineering and Earth Sciences



Introduction

- Human permanence off Earth depends on efficient, safe, and reliable transportation capabilities
- Need to test wheel-regolith interactions experimentally and be able to predict computationally
 - RIDER offers full-scale, automated rover wheel testing in relevant simulants
 - SPIDR offers realistic simulation of rover wheels in the lunar environment

RIDER Description

- 3.8 x 0.9 x 0.5 m deep simulant bin with custom compaction capabilities
- Gravity offload / load application system
 - ≤200 kg single-wheel loads
- Air filtration, dust containment, dehumidification
- Interchangeable BLDC motors (10:1, 50:1, 100:1, 225:1 reduction ratios)
- Custom wheel mounting system
 - Wheels from 26 to 82 cm diameter
- Control system logs data to ASCII text files for later analysis
- Video recording from multiple angles

SPIDR Description

- Discrete element modeling (DEM) of CAD-based wheel geometries interacting with the lunar environment (e.g., surface, electric fields, and gravity)
 - Focuses on <2 μm fraction of regolith
- Calibrated to experiments with returned Apollo samples (15071 and 61141)
 - Currently undergoing recalibration
- Predicts dust plume trajectories and velocities
 - LRV wheel and Apollo 16 Grand Prix

RIDER




Figure 1-9. 1) RIDER at the UCF Exolith Lab (inset: motor box and wheel hub); 2) Control system (inset: electronics box and data logging system); 3) Camera in custom mount; 4) Dehumidifier and air filters; 5) G. Blandin in PAPR respirator; 6-8) Simplified LHS-1 in RIDER before (6), during (7) and after (8) compaction; 9) Testing Astrobotic Polaris prototype wheel in illuminated, dust mitigated, dehumidified bin.



SPIDR




Figure 10-13. 10) a diagram of the column collapse experiments used to calibrate SPIDR; 11) Images of the lunar samples in different stages of column collapse with yellow lines showing measurement heights; 12) DEM simulations of collapse experiments compared to laboratory experiments with lunar samples; 13) CAD-based wheel (LRV) geometry ingested into simulation with lunar-like particles and environmental conditions

RIDER and SPIDR as Services

- RIDER and SPIDR offer unparalleled planetary terramechanics testing capabilities and serve to cross-validate each other's findings
- RIDER provides:
 - Experimental evaluation of rover wheel performance (e.g., longevity, slip, sinkage) in high-fidelity, customizable simulants
 - Testing of rover wheels customer-specified speeds and loads
 - Capabilities to analyze traffic-induced effects on the regolith
- SPIDR provides:
 - Computational evaluation of rover wheel performance and optimal drive speed (travel efficiency and dust mitigation)
 - Ability to simulate rover traffic on any planetary body
 - Upcoming calibrations for Mars
- RIDER and SPIDR teams can comply with any privacy measures (nondisclosure agreements, visual barriers, etc.)
- Reach out to jared.long-fox@ucf.edu or dbritt@ucf.edu for more information, logistics, and scheduling

Acknowledgements

- Supported NASA Cooperative Agreement 80NSSC19M0214 to the UCF Center for Lunar and Asteroid Surface Science (SServi/CLASS)
- Thanks to Colin Creager at NASA GRC for LRV and Resource Prospector wheel loans for initial RIDER testing
- Thanks to Mike Provenzano at Astrobotic for Polaris prototype wheel loan for initial RIDER testing
- Thanks to Ron Creel for LRV wheel and fender CAD files and information