



# Lunar Underactuated Arm (LUnA) Project

E.J Wiendczak, A.G Levi, J.D.Taggard, J.M. Collins, and B.C. Hicks

Presentation to the Space Resources Roundtable XXIV, 04 - 07 June 2024, Golden CO

Alejandro Levi

Senior Systems Engineer, Maxar Space Robotics

Graduate Student, Space Resources, Colorado School of Mines

Public – External Recipients







# Lunar Underactuated Arm (LUnA) Project Overview



- Explored feasibility of maturing minimal/underactuated robotic arm technology
- LUnA is a 4 Degrees-of-Freedom (DOF) arm with a single actuator at the shoulder.
- Movement at each joint controlled by a brake subsystem.
- Effort bridged Technology Readiness Level (TRL) 4 (Breadboard validation in a laboratory environment) to TRL 6 (Prototype demonstrated in a relevant environment).
- Design is scalable up to 7 DOF with a single actuator
- Use of a single actuator at the shoulder -- benefits:
  - Better thermal and radiation protection.
  - Reduced mass, power, and recurring cost.
- Payload deployment and retrieval use case was selected to demonstrate technology.
- Relevant environments included
  - Demonstration under thermal/vacuum conditions.
  - Demonstration at the Colorado School of Mines Lunar Testbed Facility to validate dust mitigation techniques.





# Minimal Actuation Concept

- Typical robotic arms are fully actuated, i.e., an actuator exists at each joint.
- An underactuated arm has less actuators than joints.
- LUnA is a *minimally* actuated arm; it has a single actuator at the base and a series of drive tapes and brakes that control the joints.
- Torque from the actuator is transmitted to the four joints of the arm (in a Yaw-Pitch-Pitch-Pitch configuration) equally via a drivetrain system.
- Joints move one at a time, depending on which brake is unlocked.
- *Single actuator at shoulder allows for better thermal and radiation protection of sensitive avionics, and potential mass and cost savings.*








# Demonstration Campaign

- Selected use case for demonstrations was Pick-and-Place.
  - 2kg and 4kg payloads placed at various locations from arm base.
  - This allowed the arm to navigate to them for the pickup and move operation.
  - Linux laptop running control software was located alongside and connected via the arms bulkhead connection.
- Three demonstrations:
  1. Prototype demonstrated in laboratory environment – TRL 5.
  2. Prototype demonstrated in relevant environment (Thermal/Vacuum) – TRL 6.
  3. Prototype demonstrated in relevant environment (Lunar Dust) – TRL 6.







# Demonstration 1: Laboratory Environment

- Demonstration of use case in a laboratory environment
- Acceptance criteria for this demonstration were:
  - LUnA arm provides all telemetry without faults and at 100Hz or better.
  - The payload was successfully engaged and carried throughout test motions and deployed on the desired target.
  - The test scripts returned successfully without faults.
  - All test data was collected without interruption and stored for data reduction.








## Demonstration 2: Thermal / Vacuum (TRL6)

- Demonstration of use case in a relevant environment (-40C to +65C).
- Functional checkout at 20C under vacuum
- The next demonstration setpoint was at -40C, followed by the last setpoint of +65C.
- Quick functional check performed from ambient to cold at 10C, -10C, and -30C and involved moving each joint 4° forward and back to verify arm function.
- Also performed from the cold to hot at +30C, +40C, +50C, and +60C.
- Acceptance criteria for this demonstration were the same as Demo 1 and evaluated at the three operational temperature setpoints.
- Drive train mechanics, trajectory algorithms, and tensioning performed well at ambient and cold.
- There were challenges at high temperatures holding the pretension torques and handling the same movements (i.e., picking up the payload and manipulating it).



LUnA D2 +65C (30x).mp4



## Demonstration 3: Lunar Regolith Testbed (TRL6)

- Demonstration of use case in a relevant environment.
- Same operational acceptance criteria as Demos 1 and 2.
- Conducted at Lunar Testbed Facility at Colorado School of Mines.
- Demo 3A involved static dirty test where regolith was applied to the arm prior to movement.
- Demo 3B involved dynamic dirty test where regolith actively applied to the arm throughout movement.
- Simulant used was CSM-LHT-1 Lunar Highlands Type simulant, mean particle diameter of  $122.0 \pm 2.1 \mu\text{m}$ .
- Meets the intent of NASA-STD-1008
- No dust intrusion found in the actuator and arm upon disassembly, thus validating the dust mitigation design.



LUnA D3 Test B Dual View (30x).mp4

# Scooping Operations Lunar Regolith Testbed

- Opportunity to attach functional copy of scoop planned for use on upcoming SAMPLR mission.
- Able to demonstrate scooping (video) and simple trench digging (image below).
- Sieving was problematic, as LUnA was not designed to impart lateral motion.
- Information gathered during this activity will be of benefit to SAMPLR mission planning.



LUnA D3 Test C and D Dual View (30x).mp4





# Conclusions

- Overarching philosophy: development of LUnA prototype informs design of future flight article.
- Limitation of this technology is that only one joint at a time can be moved
  - Extra time is required to lock and unlock the joints between moves.
  - Unable to have a straight-line trajectory like a fully actuated arm.
- Analysis was conducted on potential “next steps” in improvements to the initial design that would improve operational effectivity in a flight-qualified robotic arm, including:
  - Optimizing the design for better mass reduction.
  - Increasing the degrees of freedom of the arm.
  - Improvements in the drivetrain and structure (e.g., designing for ease of assembly, selection of alternative components, etc.).
  - Improvements to the control system.
- Of particular interest is optimization of the braking system.
- Future Use cases:
  - Scooping and trenching
  - Deployable structures
  - Cranes



## Acknowledgements

This material is based upon work supported by National Aeronautics and Space Administration Contract No. 80LARC21CA004 issued through the NASA Science and Technology Mission Directorate.

Thanks to the Colorado School of Mines Center for Space Resources for the use of their Lunar Testbed Facility.





MAXAR.COM



# BACKUPS





# Prototype Capabilities

Parameter	Specification
Physical Attributes	
Degrees of freedom	4 (Yaw-Pitch-Pitch-Pitch)
Total Length	1.1m
Actuators	1 (Maxar Z17)
Total mass	17kg
Structural Material	Aluminum
Performance Characteristics	
Joint Torque Capability	67Nm
Joint Range of Motion	$\pm 161.8^\circ$ at all joints (hard stop limited)
Tip Force	>49N at 0.5m reach
Tip Accuracy	.015m at 0.5m reach
Tip Repeatability	.007m at 0.5m reach
Tip Velocity	>0.026 m/s
Operational Power	28W Operational, 29.5W Peak
Idle Power	9W

Parameter	Specification
Electrical	
Arm Computer	Xiphos Q7
Motor Control Board	Elmo Gold Bee MCB
Sensing	<ul style="list-style-type: none"><li>- Actuator output position</li><li>- Motor position</li><li>- Actuator output torque</li><li>- Joint position</li><li>- Joint temperature</li></ul>
Operating Voltage	32V Max
Current Limit	1.5A
Heaters	<ul style="list-style-type: none"><li>-Motor Case</li><li>-Actuator Housing</li><li>-All Joint Brakes</li></ul>
Interface	Bulkhead Micro-D Connectors at Base
Environmental	
Operational Temperature Range	-40°C to +65°C
Vacuum	10 <sup>-6</sup> Torr
Lunar Regolith Exposure	Mitigations in design to prevent intrusion