

Living off the Land

How ISRU can benefit early habitation life support systems

SPACE RESOURCES ROUNDTABLE XXV – JUNE 3-6, 2025



James E. Johnson

Ph.D. Candidate – Space Resources Program

COLORADO SCHOOL OF MINES

Advisor: Dr. Angel Abbud-Madrid

Co-advisor: Dr. George Sowers


Disclaimer: All findings and perspectives contained herein are personally held by the Author and may not represent the findings or perspectives of their employer. All research has been conducted through personal time and resources and is not sponsored through their employer.

Living off the Land – influenced by:

 Demand – O_2 & H_2O

 Impacts – Mass & Cost

 Opportunities – ISRU vs. Regenerative Life Support Systems (LSS)



Modeling Habitation Demand



- ▶ Lunar living demand is driven by:


- ▶ Mission architecture
- ▶ Habitat design

- ▶ And quantified through:

- ▶ Known consumable rates
- ▶ Captured in NASA documentation

- ▶ Demand influences:

- ▶ Mass impacts
- ▶ Cost impacts
- ▶ Breakeven analysis




Early Habitation Concepts & Assumptions

JAXA Pressurized Rover (PR)



ASI Multi-Purpose Habitat (MPH)



Consumable Rates

- ▶ NASA Human Integrated Design Handbook (HIDH)
- ▶ NASA Baseline Values and Assumptions Document (BVAD)
- ▶ Logistics Rates and Assumptions for Future Human Spaceflight Missions Beyond LEO (Lynch et al., 2023)

Mission Architecture

- ▶ 2 crew per element
- ▶ 1 mission per year with 7 to 28-day mission durations
- ▶ 3 Extravehicular Activities (EVAs) per 7-days
- ▶ Early 2030's, 10-year lifetime

Habitat Design

- ▶ Airlock (MPH)
- ▶ Cabin Depress (PR)
- ▶ 8.2 psia, 34% O₂
- ▶ Open-loop life support


Early Habitation Raw Demand



Consumable Rates


Mission Architecture
Habitat Design

Raw Demand



MISSION PARAMETERS		
Crew Size	4	crew
Mission duration	28	days
Total EVAs	3	EVAs
EVA Duration	8	hours
Total Mission #	1	missions

HABITATION DESIGN PARAMETERS		
Number of Modules	1	modules
Module (Cabin) Volume	30	m ³
Habitat Pressurization?	No	Yes/No
Airlock?	Yes	Yes/No
Airlock Volume	13	m ³
Air Save Pump?	No	Yes/No
Air Save Min Press	2.0	psia
Operating Press	8.2	psia
O ₂ Concentration	34.0%	%
Nominal Cabin Temp	70	°F



62-68% of H₂O driven by drinking & EVA cooling



>58% of O₂ based upon EVA architecture

Lifetime Totals (PR + MPH):

- 4,640 kg H₂O
- 2,250 kg O₂

Equivalent Mass Impacts

Earth-based resupply

$$ESM = M + (V \cdot V_{eq}) + (P \cdot P_{eq}) + (C \cdot C_{eq}) + (CT \cdot D \cdot CT_{eq})$$

Equivalent
System
Mass (ESM)

=

Item mass

Volume

Power

Thermal

Crew Time

x Mass Equivalency Factor, $X_{eq} = \text{kg}/X$

- ▶ Delivered mass = raw consumable mass + container mass + packaging mass
- ▶ Pressurized volume and crew time are major factors in Earth-based resupply




~18% mass increase for transport



~160% mass increase for transport


Lifetime (PR + MPH) mass impacts: ~12,000 kg



Equivalent Mass Impacts

Regenerative LSS Alternatives

- ▶ Major factors in regenerative LSS analysis
 - ▶ Pressurized volume
 - ▶ Power
 - ▶ Thermal
- ▶ Reliability & maintenance not modelled
- ▶ OGA assumes recurring H₂O demand
- ▶ WPA+UPA assumes recurring O₂ demand
- ▶ WPA+UPA+OGA has limited recurring H₂O demand




System	Mass (kg)	Power (W)	Volume (m ³)
Oxygen Generation Assy. (OGA)	676	3573	1.57
Water Processor Assy. (WPA)	1385	343	3.14
Urine Processor Assy. (UPA)		424	
TOTAL	2,061	4,340	4.71

Regenerative systems reduce consumable resupply mass by ~26-48%

Equivalent Mass Impacts

ISRU Alternatives



- ▶ Polar Water ISRU
 - ▶ Pilot-scale production (~1,125 kg/yr H₂O) provides all needed water and oxygen
- ▶ Carbothermal (O₂ from Regolith) ISRU
 - ▶ Recurring water delivery assumed
- ▶ Molten Regolith Electrolysis (MRE) ISRU
 - ▶ Recurring water delivery assumed

System	Mass (kg)	Power (W)
Polar Water (Linne et al.)*	919	4880
O ₂ from Regolith (Sanders et al.)*	906	2340
Molten Regolith Electrolysis (Schriener et al.)	518	18420

*Mass & power adjusted for deferment of liquefaction

ISRU pilot concepts average ~60% less mass than regenerative LSS with O₂ production > 4x demand

Cost Impacts

Assessing Benefits

Regression Coefficients

$$\alpha, \beta, \Xi, \delta, \varepsilon, \phi, \gamma$$



$$\text{System Cost} = \alpha Q^{\beta} M^{\Xi} \delta^S \varepsilon^{\left(\frac{1}{IOC-1900}\right)} B^{\phi} \gamma^D$$

Unit Quantity (Q)

Mass (M)

Specification (S)

Year (IOC)


Block (B)

Difficulty (D)

- ▶ Advanced Mission Cost Model (AMCM) is sensitive to difficulty (D) determination
- ▶ All regenerative LSS shows cost benefit < 39 days
- ▶ Polar water ISRU begins showing benefit over WPA+UPA architectures in 49 days
- ▶ ISRU cost advantages arise within 49-217 days

Cost breakeven with Earth-based resupply
Regenerative LSS ○ < ISRU ○

...but mass breakeven suggests
ISRU < Regenerative LSS...



Conclusion & Forward Work


Key Takeaways:

- ▶ Early habitation concepts under development exhibit local, small-scale demand **...may be addressed by ISRU**
- ▶ Impacts of habitation demand have non-trivial equivalent mass and cost impacts **...mitigated by ISRU**
- ▶ ISRU & regenerative LSS both provide opportunity to minimize impact **...but only ISRU is extensible to significant lunar economic development**

Earth-based resupply may approach >\$1.5B USD (est.) within three 28-day missions & warrants transition to ISRU and/or regenerative solutions

Forward Work:

- ▶ Capture driving model sensitivities
- ▶ Include mass and cost impacts of reliability, spares, and maintenance
- ▶ Conduct model-based systems engineering (MBSE) trade space assessment



Thank You!



James E. Johnson

Ph.D. Candidate – Space Resources Program

COLORADO SCHOOL OF MINES

jejohnso@mines.edu



References:

- [1] NASA, (2014). <https://www.nasa.gov/human-integration-design-handbook/>
- [2] Ewert, M. K., Chen, T. T. & Powell, C. D. (2022). <https://ntrs.nasa.gov/citations/20210024855>.
- [3] Lynch, C., et al. (2023). doi:10.2514/6.2023-4617.
- [4] JAXA. (2024). <https://humans-in-space.jaxa.jp/en/news/detail/003924.html>
- [5] Parsonson, A. (2024). <https://europeanspaceflight.com/thales-program-manager-shares-italian-lunar-habitat-details/>
- [6] Harris, D. W. et al. (2022). <https://ntrs.nasa.gov/citations/20220000524>
- [7] Lee, D. E. (2019). <https://ntrs.nasa.gov/citations/20190030294>
- [8] Genco, N. (2024). <https://www.fondazioneleonardo.com/stories/abitare-luna-casa-italiana>
- [9] Yamazaki, C., et al. (2024). <https://hdl.handle.net/2346/98961>
- [10] Schneider, W. F. et al. (2020). <https://hdl.handle.net/2346/86395>
- [11] Johnson, J. E. (2025). *54th ICES 2025 Preprint*
- [12] Levri, J. A., et al. (2003). <https://ntrs.nasa.gov/citations/20040021355>
- [13] Bagdigian, R.M., et al. (2015). <http://hdl.handle.net/2346/64374>
- [14] Bagdigian, R. M. & Cloud, D. (2005). doi: 10.4271/2005-01-2779.
- [15] Stromgren, C., et al. (2023). doi: 10.1109/AERO55745.2023.10115984.
- [16] Linne, D. L., Kleinhenz, J. E. & Paz, A. (2020). doi:10.2514/6.2020-4236.
- [17] Sanders, G., Kleinhenz, J. & Linne, D. (2022). <https://ntrs.nasa.gov/citations/20220008799>
- [18] Schreiner, S. S. (2015). <https://dspace.mit.edu/handle/1721.1/98589>
- [19] Guerra, L. & Shishko, R. (1999). in Human spaceflight: mission analysis and design.